



STLS Rung

The rungs STLS can be installed during the installation of the vertical ladder and bolted to the side rail. They are suitable for STU 50 vertical ladders and are 203 to 793 mm wide corresponding to the vertical ladder width. We provide components in various materials and surface finishes to ensure that the corrosion requirements are met for all sorts of applications.

steel, continuously hot galvanized/Sendzimir process

Products	H	B	L	weight
STLS 02S	22 mm	40 mm	203 mm	0,237 kg
incl.: 2 × SES 6X16, 2 × SEMS 6				
STLS 03S	22 mm	40 mm	293 mm	0,355 kg
incl.: 2 × SES 6X16, 2 × SEMS 6				
STLS 04S	22 mm	40 mm	393 mm	0,468 kg
incl.: 2 × SES 6X16, 2 × SEMS 6				
STLS 05S	22 mm	40 mm	493 mm	0,577 kg
incl.: 2 × SES 6X16, 2 × SEMS 6				
STLS 06S	22 mm	40 mm	593 mm	0,704 kg
incl.: 2 × SEMS 6, 2 × SES 6X16				
STLS 07S	22 mm	40 mm	693 mm	0,894 kg
incl.: 2 × SES 6X16, 2 × SEMS 6				
STLS 08S	22 mm	40 mm	793 mm	0,903 kg
incl.: 2 × SES 6X16, 2 × SEMS 6				

Page 1



PRODUCT INFORMATION

steel, batch/hot-dip galvanized

Products	H	B	L	weight
STLS 02F	22 mm	203 mm	40 mm	0,270 kg
incl.: 2 × SES 6X16E, 2 × SEMS 6E				
STLS 03F	22 mm	293 mm	40 mm	0,379 kg
incl.: 2 × SES 6X16E, 2 × SEMS 6E				
STLS 04F	22 mm	393 mm	40 mm	0,509 kg
incl.: 2 × SES 6X16E, 2 × SEMS 6E				
STLS 05F	22 mm	493 mm	40 mm	0,656 kg
incl.: 2 × SES 6X16E, 2 × SEMS 6E				
STLS 06F	22 mm	593 mm	40 mm	0,754 kg
incl.: 2 × SES 6X16E, 2 × SEMS 6E				
STLS 07F	22 mm	693 mm	40 mm	0,996 kg
incl.: 2 × SEMS 6E, 2 × SES 6X16E				
STLS 08F	22 mm	793 mm	40 mm	1,116 kg
incl.: 2 × SES 6X16E, 2 × SEMS 6E				

H: height

B: width

L: length

DETAIL AND APPLICATION IMAGES



PRODUCT INFORMATION

