



## STUS 50

### Rung

The rungs STUS 50 can also be attached to the vertical ladder afterwards. They can be bolted to the side rails from the inside using BL 6 corner angles. They are suitable for STU 50-3E vertical ladders and are 200 to 1200 mm wide corresponding to the vertical ladder width. They are made of stainless steel. It is not possible to install additional STUS rungs for the vertical ladder variant with SNA nail anchors.

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	H	B	L	W
STUS 50-02E	22 mm	200 mm	40 mm	0,383 kg
incl.:				
2 × BL 6E, 2 × SEM 8E, 2 × SES 8X16E, 2 × US 8X17E				
STUS 50-03E	22 mm	300 mm	40 mm	0,489 kg
incl.:				
2 × BL 6E, 2 × SEM 8E, 2 × SES 8X16E, 2 × US 8X17E				
STUS 50-04E	22 mm	400 mm	40 mm	0,606 kg
incl.:				
2 × BL 6E, 2 × SEM 8E, 2 × SES 8X16E, 2 × US 8X17E				
STUS 50-05E	22 mm	500 mm	40 mm	0,724 kg
incl.:				
2 × US 8X17E, 2 × BL 6E, 2 × SEM 8E, 2 × SES 8X16E				
STUS 50-06E	22 mm	600 mm	40 mm	0,841 kg
incl.:				
2 × BL 6E, 2 × SEM 8E, 2 × SES 8X16E, 2 × US 8X17E				
STUS 50-07E	22 mm	700 mm	40 mm	0,958 kg
incl.:				
2 × BL 6E, 2 × SEM 8E, 2 × SES 8X16E, 2 × US 8X17E				
STUS 50-08E	22 mm	800 mm	40 mm	1,076 kg
incl.:				
2 × BL 6E, 2 × SEM 8E, 2 × SES 8X16E, 2 × US 8X17E				

Page 1



# PRODUCT INFORMATION

Products	H	B	L	W
STUS 50-09E	22 mm	900 mm	40 mm	1,193 kg
incl.:				
2 x US 8X17E, 2 x BL 6E, 2 x SEM 8E, 2 x SES 8X16E				
STUS 50-10E	22 mm	1000 mm	40 mm	1,310 kg
incl.:				
2 x BL 6E, 2 x SEM 8E, 2 x SES 8X16E, 2 x US 8X17E				
STUS 50-11E	22 mm	1100 mm	40 mm	1,428 kg
incl.:				
2 x BL 6E, 2 x SEM 8E, 2 x SES 8X16E, 2 x US 8X17E				
STUS 50-12E	22 mm	1200 mm	40 mm	1,545 kg
incl.:				
2 x BL 6E, 2 x SEM 8E, 2 x SES 8X16E, 2 x US 8X17E				

**H:** height  
**B:** width  
**L:** length  
**W:** Weight per storage unit

## DETAIL AND APPLICATION IMAGES

