



U-HW

Cable clamp for fastening to flat profiles

The HF cable clamp U-HW with full-surface pressure trough made of galvanised steel and plastic half troughs made of polystyrene can route fibre-optic/high-frequency cables with a maximum diameter of 1 5/8 inches. It is suitable for fastening to flat profiles made from material max. 12 mm thick. We provide components in various materials and surface finishes to ensure that various requirements for different areas of application are met.

steel, zinc plated

Products	D	H _{max}	B	D	cables	W
20 U-HW	17 mm	53 mm	20 mm	1/2 Zoll	1	0,045 kg
32 U-HW	29 mm	68 mm	32 mm	7/8 Zoll	1	0,088 kg
44 U-HW	39 mm	83 mm	44 mm	1 1/4 Zoll	1	0,130 kg
56 U-HW	51 mm	106 mm	56 mm	1 5/8 Zoll	1	0,161 kg
20/2 U-HW	17 mm	73 mm	20 mm	1/2 Zoll	2	0,067 kg
32/2 U-HW	29 mm	102 mm	32 mm	7/8 Zoll	2	0,135 kg
44/2 U-HW	39 mm	129 mm	44 mm	1 1/4 Zoll	2	0,207 kg
56/2 U-HW	51 mm	164 mm	56 mm	1 5/8 Zoll	2	0,221 kg
20/3 U-HW	17 mm	93 mm	20 mm	1/2 Zoll	3	0,085 kg
32/3 U-HW	29 mm	136 mm	32 mm	7/8 Zoll	3	0,176 kg

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	D	H _{max}	B	D	cables	W
20 U-HW-E	17 mm	53 mm	20 mm	1/2 Zoll	1	0,043 kg
32 U-HW-E	29 mm	68 mm	32 mm	7/8 Zoll	1	0,077 kg
44 U-HW-E	39 mm	83 mm	44 mm	1 1/4 Zoll	1	0,125 kg
56 U-HW-E	51 mm	106 mm	56 mm	1 5/8 Zoll	1	0,155 kg
20/2 U-HW-E	17 mm	73 mm	20 mm	1/2 Zoll	2	0,068 kg
32/2 U-HW-E	29 mm	102 mm	32 mm	7/8 Zoll	2	0,117 kg



PRODUCT INFORMATION

Products	D	H _{max}	B	D	cables	W
44/2 U-HW-E	39 mm	129 mm	44 mm	1 1/4 Zoll	2	0,192 kg
56/2 U-HW-E	51 mm	164 mm	56 mm	1 5/8 Zoll	2	0,251 kg
20/3 U-HW-E	17 mm	93 mm	20 mm	1/2 Zoll	3	0,086 kg
32/3 U-HW-E	29 mm	136 mm	32 mm	7/8 Zoll	3	0,138 kg
44/3 U-HW-E	39 mm	176 mm	44 mm	1 1/4 Zoll	3	0,268 kg

D: clamping range

H_{max}: maximum height

B: width

D: diameter

cables: max. number of cables

W: Weight per storage unit

DETAIL AND APPLICATION IMAGES

