

UEBD2 R

Plastic dummy cover unit, 2x, round

The UEBD2 R product solutions are round dummy cover units with carpet protection frames. They are used in dry-cleaned rooms in assembly covers, UBDHB floor sockets and raised or false floor openings. They are designed for office traffic loads and are used as mounting frames for two mounting boxes. The covers and frames are made of polyamide with matt surfaces in graphite black (RAL 9011) and iron grey (RAL 7011). They are supplied with the universal fastening claw sets and have an IP protection class of IP 30 in an unused condition. Their min. installation height is 65 mm, they are 280 mm wide, have a max. load of 2 kN and installation dimensions of 260 mm.



Products	Η	H _{min}	В	E	P _{max}	IP _n	color	Т	mounting box	ø ext	weight
UEBD2-R-G	65	65	280	260	2,00	IP-30	7011	8 mm	2	280	1,457 kg
incl.:		mm	mm	mm	kN					mm	
1 × UDBS-R 4											
UEBD2-R-S	65	65	280	260	2,00			8 mm		280	1,457 kg
	mm	mm	mm	mm	kN					mm	
incl.:											
1 × UDBS	-R 4										


H: height H_{min} : minimum installation height B: width E: fitting dimension P_{max} : maximum load IP_n : IP protection level in unused condition T: Depth of flooring recess mounting box: maximum number of installable device casings \emptyset ext:








PohlCon GmbH Nobelstraße 51 | 12057 Berlin Telefon: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com

DETAIL AND APPLICATION IMAGES









OPTIONAL ACCESSORIES

UEBD R, UDBS 40-80, UDKSEB



dry maintained

DIN

Load requirements according to, DIN EN 50085





PohlCon GmbH Nobelstraße 51 | 12057 Berlin Telefon: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com



Date of issuance: 03.07.2024. Errors and technical modifications reserved.