



US

Washers, according to DIN EN ISO 7093-1 and 7089

The US washer is a versatile accessory, but is mainly used for channel-bolt connections. For example, a hot-rolled profile in combination with a hook-head t-bolt and washer requires the use of high tightening torques. The washer in accordance with DIN EN ISO 7093-1 and 7089 also ensures steel-steel contact between the attachment part and the anchor channel. It is also used for clamp connections, clamping claws and pressure bolts. US washers are available in various dimensions, hardnesses and designs (galvanised or hot-dip galvanised steel, A4 stainless steel).

Products	W
US708916 A4-70	0,010 kg
US708920 8.8 FV	0,016 kg
US708920 8.8 GV	0,014 kg
US708920 A4-70	0,016 kg
US708924 8.8 FV	0,031 kg
US708924 8.8 GV	0,028 kg
US708924 A4-70	0,029 kg
US708927 8.8 FV	0,040 kg
US708927 8.8 GV	0,037 kg
US708927 A4-70	0,001 kg
US708930 8.8 FV	0,050 kg
US708930 8.8 GV	0,048 kg
US708930 A4-70	0,001 kg
US70898 A4-70	0,003 kg
US7093-1-8 A4	0,006 kg
US708912 A4-70	0,005 kg
US7093-1-10 A4	0,012 kg
US7093-1-10 FV	0,013 kg
US7093-1-10 GV	0,012 kg
US7093-1-12 A4	0,022 kg

Page 1



PRODUCT INFORMATION

Products	W
US7093-1-12 FV	0,024 kg
US7093-1-12 GV	0,022 kg
US7093-1-16 A4	0,042 kg
US7093-1-16 FV	0,045 kg
US7093-1-16 GV	0,041 kg
US7093-1-20 A4	0,080 kg
US7093-1-20 FV	0,086 kg
US7093-1-20 GV	0,078 kg
US708910 8.8 FV	0,004 kg
US7093-1-6 GV	0,003 kg
US708910 8.8 GV	0,003 kg
US708910 A4-70	0,003 kg
US7093-1-8 GV	0,006 kg
US708912 8.8 FV	0,006 kg
US708912 8.8 GV	0,005 kg
US708916 8.8 FV	0,010 kg
US708916 8.8 GV	0,010 kg
US7093-1-6 A4	0,003 kg
US70896 A4-70	0,003 kg

W: Weight per storage unit

DETAIL AND APPLICATION IMAGES



