



US9021

Washer, DIN EN ISO 7093

The US9021 washer is a versatile accessory, but is mainly used for channel-bolt connections. For example, a hot-rolled profile in combination with a hook-head t-bolt and washer requires the use of high tightening torques. The washer also ensures steel-to-steel contact between the attachment part and the anchor channel. It is also used for clamp connections, clamping claws and pressure bolts. We provide components in various materials and surface finishes to ensure that various corrosion protection requirements for different areas of application are met.

steel, galvanic zinc plated

Products	ø	D	t	W
US 6X18	6,4 mm	18 mm	1,60 mm	0,002 kg
US 8X25	8,4 mm	24 mm	1,60 mm	0,006 kg
US 10X30	10,5 mm	30 mm	2,50 mm	0,011 kg
US 13X40	13 mm	37 mm	3,00 mm	0,018 kg

steel, batch/hot-dip galvanized

Products	ø	D	t	W
US 10X30F	10,5 mm	30 mm	2,50 mm	0,011 kg
US 13X40F	13 mm	37 mm	3,00 mm	0,020 kg

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	ø	D	t	W
US 6X18E	6,4 mm	18 mm	1,60 mm	0,002 kg
US 8X25E	8,4 mm	24 mm	1,60 mm	0,006 kg
US 10X30E	10,5 mm	30 mm	2,50 mm	0,010 kg



PRODUCT INFORMATION

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	\emptyset	D	t	W
US 8X25E4	8,4 mm	24 mm	1,60 mm	0,007 kg
US 10X30E4	10,5 mm	30 mm	2,50 mm	0,011 kg

\emptyset : inner diameter
D: diameter
t: material thickness
W: Weight per storage unit

DETAIL AND APPLICATION IMAGES

