



## WLKAB

### Wide span cable ladder outlet plate

The WLKAB wide span cable ladder outlet plate is used for the cable-protecting vertical execution of cables from the wide span cable ladder. It has a width corresponding to the cable ladder of 140 to 540 mm. Various materials and surfaces ensure that the corrosion protection requirements of a wide range of applications are met.

steel, continuously hot galvanized/Sendzimir process

Products	H	B	L	R	t	weight
WLKAB 20S	110 mm	140 mm	129 mm	100 mm	1,50 mm	0,372 kg
incl.:						
2 × FKS 6X10, 2 × AM16 M6F						
WLKAB 30S	110 mm	240 mm	129 mm	100 mm	1,50 mm	0,613 kg
incl.:						
2 × FKS 6X10, 2 × AM16 M6F						
WLKAB 40S	110 mm	340 mm	129 mm	100 mm	1,50 mm	0,854 kg
incl.:						
2 × FKS 6X10, 2 × AM16 M6F						
WLKAB 50S	110 mm	440 mm	129 mm	100 mm	1,50 mm	1,112 kg
incl.:						
3 × FKS 6X10, 3 × AM16 M6F						
WLKAB 60S	110 mm	540 mm	129 mm	100 mm	1,50 mm	1,353 kg
incl.:						
3 × FKS 6X10, 3 × AM16 M6F						

steel, batch/hot-dip galvanized

Products	H	B	L	R	t	weight
WLKAB 20F	110 mm	140 mm	129 mm	100 mm	1,50 mm	0,393 kg

Page 1



# PRODUCT INFORMATION

Products	H	B	L	R	t	weight
incl.: 2 × AM16 M6E4, 2 × FKS 6X10E						
WLKAB 30F	110 mm	240 mm	129 mm	100 mm	1,50 mm	0,651 kg
incl.: 2 × FKS 6X10E, 2 × AM16 M6E4						
WLKAB 40F	110 mm	340 mm	129 mm	100 mm	1,50 mm	0,909 kg
incl.: 2 × FKS 6X10E, 2 × AM16 M6E4						
WLKAB 50F	110 mm	440 mm	129 mm	100 mm	1,50 mm	1,183 kg
incl.: 3 × FKS 6X10E, 3 × AM16 M6E4						
WLKAB 60F	110 mm	540 mm	129 mm	100 mm	1,50 mm	1,440 kg
incl.: 3 × FKS 6X10E, 3 × AM16 M6E4						

**H:** height  
**B:** width  
**L:** length  
**R:** radius  
**t:** material thickness

## DETAIL AND APPLICATION IMAGES

