


WPDUK

Cover clamp



The cover clips WPDUK are used to secure wide-span covers on cable trays. The cover clips must be fixed 100 mm from the ends of the cover as well as in the middle of the cover. They can also be used as a storm protection bracket. At least 6 safety elements must be used per 3 metres of cable tray cover according to the installation instructions. In wind-exposed areas, the number of cover clips must be increased to at least 10. We provide components in various materials and surface finishes to ensure that various corrosion protection requirements for different areas of application are met.

steel, batch/hot-dip galvanized

Products	H	B	L1	L2	t	M	weight
WPDUK F	22 mm	20 mm	28 mm	21 mm	3,00 mm	2 Nm	0,038 kg
incl.:							
1 × SES 6X20E							

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	H	B	L1	L2	t	M	weight
WPDUK E	22 mm	20 mm	28 mm	21 mm	3,00 mm	2 Nm	0,037 kg
incl.:							
1 × SES 6X20E							

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	H	B	L1	L2	t	M	weight
WPDUK E4	22 mm	20 mm	28 mm	21 mm	3,00 mm	2 Nm	0,037 kg
incl.:							
1 × SES 6X20E4							



PRODUCT INFORMATION

H: height
B: width
L1: length 1
L2: length 2
t: material thickness
M: torque

DETAIL AND APPLICATION IMAGES

