



WPV 100

Wide-span cable tray connector, height = 95 mm

WPV 100 wide-span connectors can be used to connect wide-span cable trays or ladders together. They are 95 mm high corresponding to the height of the cable tray rail. One side of the connector is mounted as a floating bearing to allow for thermal expansion. The specified torques must be taken into observed. The other side of the connector is formed as a fixed bearing. A minimum distance of 4 mm must be maintained between the cable trays. We provide components in various materials and surface finishes to ensure that various corrosion protection requirements for different areas of application are met.

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	H	L	weight
WPV 100E	95 mm	400 mm	0,964 kg
incl.:			
4 x KLS 10X20E, 4 x FRSV 10X20E, 4 x US 10X21E, 4 x SEMSS 10E			

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	H	L	weight
WPV 100E4	95 mm	400 mm	0,977 kg
incl.:			
4 x FRSV 10X20E4, 4 x US 10X21E4, 4 x SEMSS 10E4, 4 x KLS 10X20E4			

H: height
L: length

DETAIL AND APPLICATION IMAGES



PRODUCT INFORMATION

