

# **WPVV 120**

Wide-span cable tray connector, vertical, height = 120 mm

WPVV 120 wide-span connectors can be used to connect wide-span cable trays or ladders together and to create vertical changes in direction. Both side connectors must be adjusted to the required angle and bolted in place on site before being installed. Use the slots for angles between 60 and 90°. The wide-span connectors are 115 mm high corresponding to the height of the cable tray rail. We provide components in various materials and surface finishes to ensure that various corrosion protection requirements for different areas of application are met.

#### steel, continously hot galvanized/Sendzimir process

Products	Н	L	weight	
WPVV 120S	120 mm	506 mm	1,513 kg	
incl.:				
8 × KLS 10X20,	2 × SES 10X20, 2 × SEM 10,	1 × FS 10		

#### steel, batch/hot-dip galvanized

Products	Н	L	weight			
WPVV 120F	120 mm	506 mm	1,621 kg			
incl.:						
8 × KLS 10X20F, 2 × SES 10X20F, 2 × SEM 10F, 1 × FS 10E						

H: height L: length

### DETAIL AND APPLICATION IMAGES




PohlCon GmbH Nobelstraße 51 | 12057 Berlin Telefon: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com



Page 1

## **PRODUCT INFORMATION**



→ (ABC) → (ABC) → HGF OOO	O D E O O D C BA O O O O O O O C BA O O O O C B O O C F G H O O C F G H O O O O C F G H O O O O O O C F G H O O O O O O O O O O O O O O O O O O	
	15°C + G 18°E + B 30°A + F 45°B + H 60°A + H	





PohlCon GmbH Nobelstraße 51 | 12057 Berlin Telefon: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com



Date of issuance: 03.07.2024. Errors and technical modifications reserved.