



## WPVV 150

Wide-span cable tray connector, vertical, height = 150 mm

WPVV 150 wide-span connectors can be used to connect wide-span cable trays or ladders together and to create vertical changes in direction. Both side connectors must be adjusted to the required angle and bolted in place on site before being installed. Use the slots for angles between 60 and 90°. The wide-span connectors are 145 mm high corresponding to the height of the cable tray rail. We provide components in various materials and surface finishes to ensure that various corrosion protection requirements for different areas of application are met.

steel, continuously hot galvanized/Sendzimir process

Products	H	L	weight
WPVV 150S	150 mm	754 mm	2,341 kg
incl.:			
8 × KLS 10X20, 2 × SES 10X20, 2 × SEM 10, 1 × FS 10			

steel, batch/hot-dip galvanized

Products	H	L	weight
WPVV 150F	150 mm	754 mm	2,507 kg
incl.:			
8 × KLS 10X20F, 2 × SES 10X20F, 2 × SEM 10F, 1 × FS 10E			

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	H	L	weight
WPVV 150E	150 mm	754 mm	2,379 kg
incl.:			
8 × KLS 10X20E, 2 × SES 10X20E, 2 × SEM 10E, 1 × FS 10E			



# PRODUCT INFORMATION

---

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	H	L	weight
WPVV 150E4	150 mm	754 mm	2,401 kg
incl.:			
2 x SEM 10E4, 8 x KLS 10X20E4, 2 x SES 10X20E4			

**H:** height  
**L:** length

