



FRS

round-head screw with square, DIN 603

galvanized, according to DIN EN ISO 19598 / DIN EN ISO 2081

Product	L	D	Ø	d	G
FRS 6X25	25 mm	16 mm	6 mm	4 mm	0,7 kg/100
FRS 8X20	20 mm	20 mm	8 mm	5 mm	1,4 kg/100
FRS 8X25	25 mm	20 mm	8 mm	5 mm	1,5 kg/100
FRS 8X35	35 mm	20 mm	8 mm	5 mm	1,9 kg/100
FRS 8X50	50 mm	20 mm	8 mm	5 mm	2,2 kg/100
FRS 10X30	30 mm	24 mm	10 mm	6 mm	2,8 kg/100
FRS 12X30	30 mm	30 mm	12 mm	8 mm	4,6 kg/100

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	L	D	Ø	d	G
FRS 10X30F	30 mm	24 mm	10 mm	6 mm	4,9 kg/100
FRS 12X30F	30 mm	30 mm	12 mm	8 mm	4,6 kg/100

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	L	D	Ø	d	G
FRS 6X16E	16 mm	16 mm	6 mm	4 mm	0,6 kg/100
FRS 6X20E	20 mm	16 mm	6 mm	4 mm	0,6 kg/100



Product	L	D	Ø	d	G
FRS 6X25E	25 mm	16 mm	6 mm	4 mm	0,7 kg/100
FRS 6X50E	50 mm	16 mm	6 mm	4 mm	1,4 kg/100
FRS 8X20E	20 mm	20 mm	8 mm	5 mm	1,4 kg/100
FRS 8X25E	25 mm	20 mm	8 mm	5 mm	1,5 kg/100
FRS 8X35E	35 mm	20 mm	8 mm	5 mm	1,9 kg/100
FRS 8X50E	50 mm	20 mm	8 mm	5 mm	2,2 kg/100
FRS 10X30E	30 mm	24 mm	10 mm	6 mm	2,8 kg/100
FRS 12X30E	30 mm	30 mm	12 mm	8 mm	5,1 kg/100

Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	L	D	Ø	d	G
FRS 6X20E4	20 mm	16 mm	6 mm	4 mm	0,8 kg/100
FRS 8X25E4	25 mm	20 mm	8 mm	5 mm	1,4 kg/100
FRS 8X50E4	50 mm	20 mm	8 mm	5 mm	2,3 kg/100

L: length
D: diameter
Ø: diameter
d: thickness
G: weight

DETAILS / APPLICATIONS



