



## GB

threaded rod, DIN 976-1

Stress-areas according to DIN 267-4: GB M8 = 36.6 mm<sup>2</sup>, GB M10 = 58.0 mm<sup>2</sup>, GB M12 = 84.3 mm<sup>2</sup>. The producte can be used for fire protection. For technical parameters, see National Technical Test Certificates (abPs).

galvanized, according to DIN EN ISO 19598 / DIN EN ISO 2081

Product	L	Ø	G
GB M8-03	300 mm	8 mm	8,20 kg/100
GB M8-05	500 mm	8 mm	15,30 kg/100
GB M8-10	1000 mm	8 mm	30,70 kg/100
GB M10-03	300 mm	10 mm	14,10 kg/100
GB M10-05	500 mm	10 mm	24,30 kg/100
GB M10-10	1000 mm	10 mm	49,70 kg/100
GB M12-03	300 mm	12 mm	21,70 kg/100
GB M12-05	500 mm	12 mm	36,20 kg/100
GB M12-10	1000 mm	12 mm	72,50 kg/100

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	L	Ø	G
GB M8-10E	1000 mm	8 mm	30,90 kg/100
GB M10-10E	1000 mm	10 mm	50,01 kg/100
GB M12-10E	1000 mm	12 mm	72,96 kg/100

L: length  
 Ø: diameter  
 G: weight



