



GDR

mesh cable tray cover with turning bolts

mesh cable tray cover, positive locking, with additional turning bolts

Installation of covers in outdoor areas requires additional provisions against storm forces. Turning bolts are in no case sufficient as security provision.

Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Product	B	L	G
GDR 06S	60 mm	3000 mm	2,17 kg
GDR 10S	100 mm	3000 mm	2,4 kg
GDR 20S	200 mm	3000 mm	4,15 kg
GDR 30S	300 mm	3000 mm	7,9 kg
GDR 40S	400 mm	3000 mm	10,25 kg
GDR 50S	500 mm	3000 mm	15,73 kg
GDR 60S	600 mm	3000 mm	18,67 kg

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	B	L	G
GDR 06F	60 mm	3000 mm	2,18 kg
GDR 10F	100 mm	3000 mm	2,4 kg
GDR 20F	200 mm	3000 mm	4,15 kg
GDR 30F	300 mm	3000 mm	7,9 kg
GDR 40F	400 mm	3000 mm	10,25 kg
GDR 50F	500 mm	3000 mm	15,73 kg
GDR 60F	600 mm	3000 mm	18,67 kg



Stainless steel, according to ASTM 304 / BS 304 S 3

Product	B	L	G
GDR 06E	60 mm	3000 mm	2,19 kg
GDR 10E	100 mm	3000 mm	2,6 kg
GDR 20E	200 mm	3000 mm	4,5 kg
GDR 30E	300 mm	3000 mm	7,94 kg
GDR 40E	400 mm	3000 mm	10,31 kg
GDR 50E	500 mm	3000 mm	15,16 kg
GDR 60E	600 mm	3000 mm	18,01 kg

B: width
L: length
G: weight

DETAILS / APPLICATIONS

