



HS22

tee-head bolt, A2/ A4

galvanized, according to DIN EN ISO 19598 / DIN EN ISO 2081

Product	L	Ø	G
HS22 12X30	30 mm	12 mm	9,5 kg/100
HS22 12X40	40 mm	12 mm	10 kg/100
HS22 12X50	50 mm	12 mm	10,8 kg/100
HS22 12X60	60 mm	12 mm	11,4 kg/100
HS22 16X40	40 mm	16 mm	16,2 kg/100
HS22 16X60	60 mm	16 mm	18,6 kg/100

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	L	Ø	G
HS22 10X80F	80 mm	10 mm	9,7 kg/100

Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	L	Ø	G
HS22 10X80E4	80 mm	10 mm	9,7 kg/100
HS22 12X30E4	30 mm	12 mm	9,6 kg/100
HS22 12X40E4	40 mm	12 mm	10,1 kg/100
HS22 12X50E4	50 mm	12 mm	10,9 kg/100



Product	L	Ø	G
HS22 12X60E4	60 mm	12 mm	11,5 kg/100
HS22 16X40E4	40 mm	16 mm	16,3 kg/100
HS22 16X60E4	60 mm	16 mm	18,7 kg/100

L: length
Ø: diameter
G: weight

DETAILS / APPLICATIONS

