

## KHA 82

profile rail 41x82 mm, perforated

profile rail 41x82x2.50 mm, with continuous perforation 14x30, welded back to back, slot size 22 mm

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	L	t	G
KHA 82-30F	82 mm	41 mm	3000 mm	2,50 mm	15,68 kg
KHA 82-60F	82 mm	41 mm	6000 mm	2,50 mm	31,36 kg

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	B	L	t	G
KHA 82-30E	82 mm	41 mm	3000 mm	2,50 mm	14,87 kg
KHA 82-60E	82 mm	41 mm	6000 mm	2,50 mm	29,74 kg




Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	H	B	L	t	G
KHA 82-30E4	82 mm	41 mm	3000 mm	2,50 mm	15,05 kg
KHA 82-60E4	82 mm	41 mm	6000 mm	2,50 mm	30,10 kg

**H:** height  
**B:** width  
**L:** length  
**t:** material thickness  
**G:** weight



## DETAILS / APPLICATIONS



$$\begin{aligned}W_y &= 8.64 \text{ cm}^3 \\W_z &= 8.76 \text{ cm}^3 \\I_y &= 35.41 \text{ cm}^4 \\I_z &= 17.95 \text{ cm}^4\end{aligned}$$

## OPTIONAL ACCESSORIES

AM22, SAI 41, AMF22, BGA 41/2, RUS 41

