


KHUSS 40

support piece, KHU 40

The support piece is to be used in conjunction with KDU/KHU 40.



Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Product	G
KHUSS 40S	0,11 kg
incl.:	
1x SES 10X70	hexagon head bolt, DIN 933
1x SEM 10	hexagon-nut, DIN 934
2x US 10X21	washer, DIN EN ISO 7089

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	G
KHUSS 40F	0,11 kg
incl.:	
1x SES 10X70F	hexagon head bolt, DIN 933
1x SEM 10F	hexagon-nut, DIN 934
2x US 10X21F	washer, DIN EN ISO 7089

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	G
KHUSS 40E	0,11 kg



Product	G
incl. 1x SEM 10E 1x SES 10X70E	hexagon-nut, DIN 934 hexagon head bolt, DIN 933

Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	G
KHUSS 40E4	0,11 kg
incl. 1x SEM 10E4 1x SES 10X70E4	hexagon-nut, DIN 934 hexagon head bolt, DIN 933

G: weight

