


## LIBD

cable ladder inside bend cover

cover for cable ladder inside bends



### Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Product	B	R	t	G
LIBD 20S	204 mm	398 mm	0,75 mm	1,33 kg
LIBD 30S	304 mm	398 mm	1,00 mm	2,75 kg
LIBD 40S	404 mm	398 mm	1,00 mm	3,87 kg
LIBD 50S	504 mm	398 mm	1,25 mm	6,38 kg
LIBD 60S	604 mm	398 mm	1,25 mm	8,09 kg

### Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	B	R	t	G
LIBD 20F	204 mm	398 mm	0,75 mm	1,42 kg
LIBD 30F	304 mm	398 mm	1,00 mm	2,94 kg
LIBD 40F	404 mm	398 mm	1,00 mm	4,14 kg
LIBD 50F	504 mm	398 mm	1,25 mm	6,83 kg
LIBD 60F	604 mm	398 mm	1,25 mm	8,66 kg

### Stainless steel, according to ASTM 304 / BS 304 S 3

Product	B	R	t	G
LIBD 20E	204 mm	398 mm	0,80 mm	1,43 kg



Product	B	R	t	G
LIBD 30E	304 mm	398 mm	1,00 mm	2,77 kg
LIBD 40E	404 mm	398 mm	1,00 mm	3,9 kg
LIBD 50E	504 mm	398 mm	1,25 mm	6,42 kg
LIBD 60E	604 mm	398 mm	1,25 mm	8,14 kg

**B:** width  
**R:** radius  
**t:** material thickness  
**G:** weight

