


## LIBDR

cable ladder inside bend cover with turning bolts

cover for cable ladder inside bends



### Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Product	B	R	t	G
LIBDR 20S	204 mm	398 mm	0,75 mm	1,42 kg
LIBDR 30S	304 mm	398 mm	1,00 mm	2,84 kg
LIBDR 40S	404 mm	398 mm	1,00 mm	3,96 kg
LIBDR 50S	504 mm	398 mm	1,25 mm	6,46 kg
LIBDR 60S	604 mm	398 mm	1,25 mm	8,18 kg

### Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	B	R	t	G
LIBDR 20F	204 mm	398 mm	0,75 mm	1,53 kg
LIBDR 30F	304 mm	398 mm	1,00 mm	3,04 kg
LIBDR 40F	404 mm	398 mm	1,00 mm	4,24 kg
LIBDR 50F	504 mm	398 mm	1,25 mm	6,92 kg
LIBDR 60F	604 mm	398 mm	1,25 mm	8,75 kg

### Stainless steel, according to ASTM 304 / BS 304 S 3

Product	B	R	t	G
LIBDR 20E	204 mm	398 mm	0,80 mm	1,44 kg



Product	B	R	t	G
LIBDR 30E	304 mm	398 mm	1,00 mm	2,87 kg
LIBDR 40E	404 mm	398 mm	1,00 mm	4,00 kg
LIBDR 50E	504 mm	398 mm	1,25 mm	6,52 kg
LIBDR 60E	604 mm	398 mm	1,25 mm	8,24 kg

**B:** width  
**R:** radius  
**t:** material thickness  
**G:** weight

## DETAILS / APPLICATIONS

