


## RBVDR

cable tray bend cover, variable with turning bolts

cable tray bend cover, positive locking, with additional turning bolts



### Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Product	B	G
RBVDR 05S	50 mm	0,09 kg
RBVDR 10S	100 mm	0,15 kg
RBVDR 20S	200 mm	0,40 kg
RBVDR 30S	300 mm	0,77 kg
RBVDR 40S	400 mm	1,26 kg
RBVDR 50S	500 mm	1,88 kg
RBVDR 60S	600 mm	2,62 kg

### Stainless steel, according to ASTM 304 / BS 304 S 3

Product	B	G
RBVDR 05E	50 mm	0,09 kg
RBVDR 10E	100 mm	0,13 kg
RBVDR 20E	200 mm	0,38 kg
RBVDR 30E	300 mm	0,76 kg
RBVDR 40E	400 mm	1,27 kg
RBVDR 50E	500 mm	1,90 kg
RBVDR 60E	600 mm	2,65 kg



Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	B	G
RBVDR 05E4	50 mm	0,09 kg
RBVDR 10E4	100 mm	0,13 kg
RBVDR 20E4	200 mm	0,38 kg
RBVDR 30E4	300 mm	0,76 kg
RBVDR 40E4	400 mm	1,27 kg
RBVDR 50E4	500 mm	1,90 kg
RBVDR 60E4	600 mm	2,65 kg

**B:** width  
**G:** weight

## DETAILS / APPLICATIONS

