



RU-HW

cable clamp for fastening to round and flat profiles

HF cable clamp with all-over vat made of galvanised steel and plastic half-vats made of polystyrene. For fastening to round and flat profiles with a material thickness of up to 22 mm.

Zinc coated

Product	B	D	H _{max}	number of cables	G
20 RU-HW	20 mm	1/2 inch	53 mm	1	5,82 kg/100
32 RU-HW	32 mm	7/8 inch	68 mm	1	11,4 kg/100
44 RU-HW	44 mm	1 1/4 inch	83 mm	1	15,7 kg/100
56 RU-HW	56 mm	1 5/8 inch	106 mm	1	21,72 kg/100
20/2 RU-HW	20 mm	1/2 inch	73 mm	2	8,64 kg/100
32/2 RU-HW	32 mm	7/8 inch	102 mm	2	16,9 kg/100
44/2 RU-HW	44 mm	1 1/4 inch	129 mm	2	23,24 kg/100
56/2 RU-HW	56 mm	1 5/8 inch	164 mm	2	29,24 kg/100
20/3 RU-HW	20 mm	1/2 inch	93 mm	3	12,8 kg/100
32/3 RU-HW	32 mm	7/8 inch	136 mm	3	25 kg/100
44/3 RU-HW	44 mm	1 1/4 inch	176 mm	3	34,4 kg/100

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	B	D	H _{max}	number of cables	G
20 RU-HW-E	20 mm	1/2 inch	53 mm	1	5,72 kg/100
32 RU-HW-E	32 mm	7/8 inch	68 mm	1	11,1 kg/100
44 RU-HW-E	44 mm	1 1/4 inch	83 mm	1	14,6 kg/100
56 RU-HW-E	56 mm	1 5/8 inch	106 mm	1	18,5 kg/100
20/2 RU-HW-E	20 mm	1/2 inch	73 mm	2	7,94 kg/100



Product	B	D	H _{max}	number of cables	G
32/2 RU-HW-E	32 mm	7/8 inch	102 mm	2	16,7 kg/100
44/2 RU-HW-E	44 mm	1 1/4 inch	129 mm	2	22,6 kg/100
56/2 RU-HW-E	56 mm	1 5/8 inch	164 mm	2	29,3 kg/100
20/3 RU-HW-E	20 mm	1/2 inch	93 mm	3	10,4 kg/100
32/3 RU-HW-E	32 mm	7/8 inch	136 mm	3	22,1 kg/100
44/3 RU-HW-E	44 mm	1 1/4 inch	176 mm	3	30,6 kg/100

B: width

D: diameter

H_{max}: Maximum height

number of cables: Maximum number of installable cables

G: weight

DETAILS / APPLICATIONS

