



## S-HW

cable clamp for fastening to angle profiles

HF cable clamp with all-over vat made of galvanised steel and plastic half-vats made of polystyrene. For fastening to angle profiles with a side length of up to max. 43 mm.

### Zinc coated

Product	B	D	D	H <sub>max</sub>	number of cables	G
20 S-HW	20 mm	20 mm	1/2 inch	53 mm	1	5,52 kg/100
32 S-HW	32 mm	32 mm	7/8 inch	68 mm	1	8,6 kg/100
44 S-HW	44 mm	44 mm	1 1/4 inch	83 mm	1	14,9 kg/100
56 S-HW	56 mm	56 mm	1 5/8 inch	106 mm	1	18,22 kg/100
20/2 S-HW	20 mm	20 mm	1/2 inch	73 mm	2	6,44 kg/100
32/2 S-HW	32 mm	32 mm	7/8 inch	102 mm	2	13,3 kg/100
20/3 S-HW	20 mm	20 mm	1/2 inch	93 mm	3	8,66 kg/100

### Stainless steel, according to ASTM 304 / BS 304 S 3

Product	B	D	D	H <sub>max</sub>	number of cables	G
20 S-HW-E	20 mm	20 mm	1/2 inch	53 mm	1	5,12 kg/100
32 S-HW-E	32 mm	32 mm	7/8 inch	68 mm	1	8,8 kg/100
44 S-HW-E	44 mm	44 mm	1 1/4 inch	83 mm	1	13,3 kg/100
56 S-HW-E	56 mm	56 mm	1 5/8 inch	106 mm	1	17,5 kg/100
20/2 S-HW-E	20 mm	20 mm	1/2 inch	73 mm	2	7,44 kg/100
32/2 S-HW-E	32 mm	32 mm	7/8 inch	102 mm	2	13,5 kg/100
44/2 S-HW-E	44 mm	44 mm	1 1/4 inch	129 mm	2	20,1 kg/100
56/2 S-HW-E	56 mm	56 mm	1 5/8 inch	164 mm	2	26,8 kg/100
20/3 S-HW-E	20 mm	20 mm	1/2 inch	93 mm	3	9,3 kg/100



Product	B	D	D	H <sub>max</sub>	number of cables	G
32/3 S-HW-E	32 mm	32 mm	7/8 inch	136 mm	3	17,7 kg/100
44/3 S-HW-E	44 mm	44 mm	1 1/4 inch	176 mm	3	26,9 kg/100

**B:** width  
**D:** diameter  
**D:** diameter  
**H<sub>max</sub>:** Maximum height  
**number of cables:** Maximum number of installable cables  
**G:** weight

## DETAILS / APPLICATIONS

