


# SEMSS

hexagon-nut, self-locking, DIN 985



galvanized, according to DIN EN ISO 19598 / DIN EN ISO 2081

Product	Ø	t	SW	G
SEMSS 5	5 mm	5,00 mm	8 mm	0,2 kg/100
SEMSS 6	6 mm	6,00 mm	10 mm	0,2 kg/100
SEMSS 8	8 mm	8,00 mm	13 mm	0,45 kg/100
SEMSS 10	10 mm	10,00 mm	17 mm	1,1 kg/100

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	Ø	t	SW	G
SEMSS 6E	8 mm	8,00 mm	13 mm	0,20 kg/100
SEMSS 8E	8 mm	8,00 mm	13 mm	0,45 kg/100
SEMSS 10E	10 mm	10,00 mm	17 mm	1,1 kg/100

Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	Ø	t	SW	G
SEMSS 6E4	6 mm	6,00 mm	10 mm	0,2 kg/100
SEMSS 8E4	8 mm	8,00 mm	13 mm	0,45 kg/100
SEMSS 10E4	10 mm	10,00 mm	17 mm	1,0 kg/100



Ø: diameter  
t: material thickness  
SW: wrench size  
G: weight

## DETAILS / APPLICATIONS

