



ST-RD

cable tray cover

cable tray cover, positive locking

To increase the cover, you need the cover elevator STD-A and the corresponding mounting accessories. This article is available made in material No. 1.4571/1.4404 (V4A) stainless steel finish.

Continuously hot galvanized (Senzimir process) (DIN EN 10346)

Product	B	L	G
RD 05S	50 mm	3000 mm	1,52 kg
RD 10S	100 mm	3000 mm	2,40 kg
RD 20S	200 mm	3000 mm	4,17 kg
RD 30S	300 mm	3000 mm	7,91 kg
RD 40S	400 mm	3000 mm	10,27 kg
RD 50S	500 mm	3000 mm	15,78 kg
RD 60S	600 mm	3000 mm	18,72 kg

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	B	L	G
RD 05F	50 mm	3000 mm	1,63 kg
RD 10F	100 mm	3000 mm	2,57 kg
RD 20F	200 mm	3000 mm	4,46 kg
RD 30F	300 mm	3000 mm	8,47 kg
RD 40F	400 mm	3000 mm	10,99 kg
RD 50F	500 mm	3000 mm	16,88 kg
RD 60F	600 mm	3000 mm	20,03 kg



Stainless steel, according to ASTM 304 / BS 304 S 3

Product	B	L	G
RD 05E	50 mm	3000 mm	1,63 kg
RD 10E	100 mm	3000 mm	2,58 kg
RD 20E	200 mm	3000 mm	4,47 kg
RD 30E	300 mm	3000 mm	7,96 kg
RD 40E	400 mm	3000 mm	10,33 kg
RD 50E	500 mm	3000 mm	15,88 kg
RD 60E	600 mm	3000 mm	18,84 kg

B: width
L: length
G: weight

DETAILS / APPLICATIONS

