



STU 50-3E

vertical cable ladder, equal U-profile

vertical ladder, medium building class, with continuously perforated side beams, for fastening directly to walls, riveted rungs made of profile rails 40x22 mm to be screwed in.

Beams and rungs are delivered not mounted including screws and nuts. This article is available made in material No. 1.4571/1.4404 (V4A) stainless steel finish. The cover RD can only be mounted in conjunction with the cover extension STD-A.

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	B1	B2	L	t	P _{max}	G
STU 50-03-3E	50 mm	300 mm	156 mm	3000 mm	2 mm	2,0 kN	10,9 kg
incl.: 2x KHU 50-30E 5x STUS 50-03E							
			bracket support, 50x22 mm rung				
STU 50-04-3E	50 mm	400 mm	356 mm	3000 mm	2 mm	2,0 kN	11,4 kg
incl.: 2x KHU 50-30E 5x STUS 50-04E							
			bracket support, 50x22 mm rung				
STU 50-05-3E	50 mm	500 mm	456 mm	3000 mm	2 mm	2,0 kN	11,9 kg
incl.: 2x KHU 50-30E 5x STUS 50-05E							
			bracket support, 50x22 mm rung				
STU 50-06-3E	50 mm	600 mm	556 mm	3000 mm	2 mm	2,0 kN	12,4 kg
incl.: 2x KHU 50-30E 5x STUS 50-06E							
			bracket support, 50x22 mm rung				
STU 50-07-3E	50 mm	700 mm	656 mm	3000 mm	2 mm	2,0 kN	12,9 kg
incl.: 2x KHU 50-30E 5x STUS 50-07E							
			bracket support, 50x22 mm rung				
STU 50-08-3E	50 mm	800 mm	756 mm	3000 mm	2 mm	2,0 kN	13,5 kg
incl.: 2x KHU 50-30E 5x STUS 50-08E							
			bracket support, 50x22 mm rung				

Page 1



Product	H	B1	B2	L	t	P _{max}	G
STU 50-02-3E	3000 mm	2,0 kN	10,4 kg				
incl.:							
2x KHU 50-30E		bracket support, 50x22 mm					
5x STUS 50-02E		rung					

H: height
B1: width
B2: width
L: length
t: material thickness
P_{max}: Maximum load
G: weight

OPTIONAL ACCESSORIES

AC, LGV 50, STR 50, STR 110, STD-A, ST-RD, BL 4, LH, SU 50/22

