



## U-HW

cable clamp for fastening to flat sections

HF cable clamp with all-over vat made of galvanised steel and plastic half-vats made of polystyrene. For fastening to flat profiles with a material thickness of up to 12 mm.

### Zinc coated

Product	B	D	H <sub>max</sub>	number of cables	G
20 U-HW	20 mm	1/2 inch	53 mm	1	4,72 kg/100
32 U-HW	32 mm	7/8 inch	68 mm	1	9,3 kg/100
44 U-HW	44 mm	1 1/4 inch	83 mm	1	14,2 kg/100
56 U-HW	56 mm	1 5/8 inch	106 mm	1	17,52 kg/100
20/2 U-HW	20 mm	1/2 inch	73 mm	2	6,84 kg/100
32/2 U-HW	32 mm	7/8 inch	102 mm	2	14,1 kg/100
44/2 U-HW	44 mm	1 1/4 inch	129 mm	2	21,8 kg/100
56/2 U-HW	56 mm	1 5/8 inch	164 mm	2	27,64 kg/100
20/3 U-HW	20 mm	1/2 inch	93 mm	3	8,96 kg/100
32/3 U-HW	32 mm	7/8 inch	136 mm	3	21,8 kg/100

### Stainless steel, according to ASTM 304 / BS 304 S 3

Product	B	D	H <sub>max</sub>	number of cables	G
20 U-HW-E	20 mm	1/2 inch	53 mm	1	4,62 kg/100
32 U-HW-E	32 mm	7/8 inch	68 mm	1	8,5 kg/100
44 U-HW-E	44 mm	1 1/4 inch	83 mm	1	13 kg/100
56 U-HW-E	56 mm	1 5/8 inch	106 mm	1	16,6 kg/100
20/2 U-HW-E	20 mm	1/2 inch	73 mm	2	6,64 kg/100
32/2 U-HW-E	32 mm	7/8 inch	102 mm	2	12,5 kg/100



Product	B	D	H <sub>max</sub>	number of cables	G
44/2 U-HW-E	44 mm	1 1/4 inch	129 mm	2	19,9 kg/100
56/2 U-HW-E	56 mm	1 5/8 inch	164 mm	2	26,6 kg/100
20/3 U-HW-E	20 mm	1/2 inch	93 mm	3	8,6 kg/100
32/3 U-HW-E	32 mm	7/8 inch	136 mm	3	16,8 kg/100
44/3 U-HW-E	44 mm	1 1/4 inch	176 mm	3	26,8 kg/100

**B:** width

**D:** diameter

**H<sub>max</sub>:** Maximum height

**number of cables:** Maximum number of installable cables

**G:** weight

## DETAILS / APPLICATIONS

