


UBDHB250 2R

hollow space floor box, double, round



Hollow space floor box, consists of a Sendzimir hot-dip galvanized steel sheet box with four bendable side walls and grounding clamp for subsonic-noise free and height-undependable assembly, can be used as pull- and installation box, openings for insertion of a shuttering unit that will be replaced with a round plastic installation unit during final assembly.

material	sheet steel, hot-dip galvanized
type of assembly	Mounting on raw concrete ceiling
application area	screed-covered duct system, for ducts up to 250 mm width
permits	according to VDE / TÜV
norm	according to DIN EN 50085


Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Product	H	H _{min}	B1	B2	L1	L2	E	mounting box	G
UBDHB250 28-259R	31 mm	67 mm	385 mm	400 mm	385 mm	400 mm	260 mm	double	3,1 kg
incl.:			grounding clamp						
1x UBDHB-Z									
UBDHB250 38-259R	41 mm	77 mm	385 mm	400 mm	385 mm	400 mm	260 mm	double	3,2 kg
incl.:			grounding clamp						
1x UBDHB-Z									
UBDHB250 48-259R	51 mm	87 mm	385 mm	400 mm	385 mm	400 mm	260 mm	double	3,3 kg
incl.:			grounding clamp						
1x UBDHB-Z									



H: height
H_{min}: Minimum installation height
B1: width
B2: width
L1: length 1
L2: length 2
E: fitting dimension
mounting box: Maximum number of installable device casings.
G: weight

DETAILS / APPLICATIONS



OPTIONAL ACCESSORIES

USR, UN

