



## WL(VV) 200

wide-span connector, vertical, height = 200 mm

Suitable for wide-span cable tray WL(R) 200.

Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Product	H	B	L	t	G
WL(VV) 200S	203 mm	26 mm	756 mm	2,50 mm	3,73 kg
incl.:					
1x SES 12X20	hexagon head bolt, DIN 933				
1x FS 12	serrated lock washer				
1x SEM 12	hexagon-nut, DIN 934				
8x FRSV 10X20	round-head screw with short square, DIN 603				
8x SEMS 10	hexagon-nut with flange, DIN EN 1661				

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	L	t	G
WL(VV) 200F	203 mm	26 mm	756 mm	2,50 mm	4,00 kg
incl.:					
1x SES 12X20F	hexagon head bolt, DIN 933				
1x FS 12E	serrated lock washer				
1x SEM 12F	hexagon-nut, DIN 934				
8x FRSV 10X20F	round-head screw with short square, DIN 603				
8x SEM 10F	hexagon-nut, DIN 934				

**H:** height  
**B:** width  
**L:** length  
**t:** material thickness  
**G:** weight



## DETAILS / APPLICATIONS

