


WPLA 150

wide-span branch, height = 150 mm

wide-span branch, formed component, integrated connectors included

Formed components must be supported at all sides. This article is available made in material No. 1.4571/1.4404 (V4A) stainless steel finish.



Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	R	G
WPLA 150-20F	150 mm	200 mm	450 mm	18,99 kg
incl.: 12x KLS 10X20F clamp fastening set				
WPLA 150-30F	150 mm	300 mm	450 mm	20,14 kg
incl.: 12x KLS 10X20F clamp fastening set				
WPLA 150-40F	150 mm	400 mm	450 mm	21,18 kg
incl.: 12x KLS 10X20F clamp fastening set				
WPLA 150-50F	150 mm	500 mm	450 mm	22,21 kg
incl.: 12x KLS 10X20F clamp fastening set				
WPLA 150-60F	150 mm	600 mm	450 mm	23,66 kg
incl.: 12x KLS 10X20F clamp fastening set				

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	B	R	G
WPLA 150-20E	150 mm	200 mm	450 mm	17,90 kg



Product	H	B	R	G
incl.: 12x KLS 10X20E				clamp fastening set
WPLA 150-30E	150 mm	300 mm	450 mm	1,99 kg
incl.: 12x KLS 10X20E				clamp fastening set
WPLA 150-40E	150 mm	400 mm	450 mm	19,97 kg
incl.: 12x KLS 10X20E				clamp fastening set
WPLA 150-50E	150 mm	500 mm	450 mm	20,94 kg
incl.: 12x KLS 10X20E				clamp fastening set
WPLA 150-60E	150 mm	600 mm	450 mm	22,31 kg
incl.: 12x KLS 10X20E				clamp fastening set

H: height
B: width
R: radius
G: weight

OPTIONAL ACCESSORIES

WPAD, WPTRV 150



UL classified

