



## WPLF 150

wide-span outside riser, height = 150 mm

wide-span outside riser 90° for vertical change of direction, with integrated connectors

Formed components must be supported at all sides. This article is available made in material No. 1.4571/1.4404 (V4A) stainless steel finish.



Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	R	G
WPLF 150-20F	150 mm	200 mm	450 mm	12,07 kg
incl.: 8x KLS 10X20F clamp fastening set				
WPLF 150-30F	150 mm	300 mm	450 mm	12,43 kg
incl.: 8x KLS 10X20F clamp fastening set				
WPLF 150-40F	150 mm	400 mm	450 mm	12,8 kg
incl.: 8x KLS 10X20F clamp fastening set				
WPLF 150-50F	150 mm	500 mm	450 mm	13,17 kg
incl.: 8x KLS 10X20F clamp fastening set				
WPLF 150-60F	150 mm	600 mm	450 mm	13,53 kg
incl.: 8x KLS 10X20F clamp fastening set				

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	B	R	G
WPLF 150-20E	150 mm	200 mm	450 mm	11,65 kg



Product	H	B	R	G
incl.: 8x KLS 10X20E				clamp fastening set
WPLF 150-30E	150 mm	300 mm	450 mm	12 kg
incl.: 8x KLS 10X20E				clamp fastening set
WPLF 150-40E	150 mm	400 mm	450 mm	12,35 kg
incl.: 8x KLS 10X20E				clamp fastening set
WPLF 150-50E	150 mm	500 mm	450 mm	12,69 kg
incl.: 8x KLS 10X20E				clamp fastening set
WPLF 150-60E	150 mm	600 mm	450 mm	13,04 kg
incl.: 8x KLS 10X20E				clamp fastening set

**H:** height  
**B:** width  
**R:** radius  
**G:** weight

## OPTIONAL ACCESSORIES

WPFD



UL classified

