



WPLS 150

wide-span inside riser, height = 150 mm

wide-span inside riser 90° for vertical change of direction, with integrated connectors

Formed components must be supported at all sides. This article is available made in material No. 1.4571/1.4404 (V4A) stainless steel finish.



Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	R	G
WPLS 150-20F	150 mm	200 mm	450 mm	10,34 kg
incl.: 8x KLS 10X20F		clamp fastening set		
WPLS 150-30F	150 mm	300 mm	450 mm	10,71 kg
incl.: 8x KLS 10X20F		clamp fastening set		
WPLS 150-40F	150 mm	400 mm	450 mm	11,08 kg
incl.: 8x KLS 10X20F		clamp fastening set		
WPLS 150-50F	150 mm	500 mm	450 mm	11,45 kg
incl.: 8x KLS 10X20F		clamp fastening set		
WPLS 150-60F	150 mm	600 mm	450 mm	11,81 kg
incl.: 8x KLS 10X20F		clamp fastening set		

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	B	R	G
WPLS 150-20E	150 mm	200 mm	450 mm	9,73 kg



Product	H	B	R	G
incl.: 8x KLS 10X20E				clamp fastening set
WPLS 150-30E	150 mm	300 mm	450 mm	10,07 kg
incl.: 8x KLS 10X20E				clamp fastening set
WPLS 150-40E	150 mm	400 mm	450 mm	10,42 kg
incl.: 8x KLS 10X20E				clamp fastening set
WPLS 150-50E	150 mm	500 mm	450 mm	10,76 kg
incl.: 8x KLS 10X20E				clamp fastening set
WPLS 150-60E	150 mm	600 mm	450 mm	11,11 kg
incl.: 8x KLS 10X20E				clamp fastening set

H: height

B: width

R: radius

G: weight

OPTIONAL ACCESSORIES

WPSD



UL classified

