



WPSD

wide-span inside riser cover

cover for wide-span inside riser

If the cover is to be mounted elevated, this must be mentioned separately in your order, e.g. WPFDA ("A" - German "aufgeständert" means elevated) This article is available made in material No. 1.4571/1.4404 (V4A) stainless steel finish.

Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

| Product | B | R | G |
|----------|--------|--------|---------|
| WPSD 20S | 200 mm | 450 mm | 1,91 kg |
| WPSD 30S | 300 mm | 450 mm | 3,5 kg |
| WPSD 40S | 400 mm | 450 mm | 4,48 kg |
| WPSD 50S | 500 mm | 450 mm | 6,81 kg |
| WPSD 60S | 600 mm | 450 mm | 8,03 kg |

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

| Product | B | R | G |
|----------|--------|--------|---------|
| WPSD 20F | 200 mm | 450 mm | 2,04 kg |
| WPSD 30F | 300 mm | 450 mm | 3,75 kg |
| WPSD 40F | 400 mm | 450 mm | 4,79 kg |
| WPSD 50F | 500 mm | 450 mm | 7,29 kg |
| WPSD 60F | 600 mm | 450 mm | 8,59 kg |

Stainless steel, according to ASTM 304 / BS 304 S 3

| Product | B | R | G |
|----------|--------|--------|---------|
| WPSD 20E | 200 mm | 450 mm | 1,91 kg |



| Product | B | R | G |
|----------|--------|--------|---------|
| WPSD 30E | 300 mm | 450 mm | 3,5 kg |
| WPSD 40E | 400 mm | 450 mm | 4,48 kg |
| WPSD 50E | 500 mm | 450 mm | 6,81 kg |
| WPSD 60E | 600 mm | 450 mm | 8,03 kg |

B: width
R: radius
G: weight

DETAILS / APPLICATIONS

| WPFDK / WPFDKA | | WPFDK / WPFDKA | |
|-------------------|----|-------------------|----|
| WPAD 20 - WPAD 60 | 6x | WPAD 20 - WPAD 60 | 6x |
| WPBD 20 - WPBD 40 | 4x | WPBD 20 - WPBD 40 | 4x |
| WPBD 50 - WPBD 60 | 5x | WPBD 50 - WPBD 60 | 5x |
| WPF 20 - WPF 60 | 4x | WPF 20 - WPF 60 | 4x |
| WPKD 20 - WPKD 60 | 8x | WPKD 20 - WPKD 60 | 8x |
| WPSD 20 - WPSD 60 | 4x | WPSD 20 - WPSD 60 | 4x |

