



## WPV 150

wide-span connector, height = 145 mm

In order to compensate for the heat expansion one side of the connector is mounted as a loose bearing. The given torques must be observed. The other side of the connector is to be mounted as a fixed bearing. A minimum distance of 4mm must be kept between the cable ladders. This article is available made in material No. 1.4571/1.4404 (V4A) stainless steel finish.

### Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Product	H	L	G
WPV 150S	150 mm	600 mm	1,79 kg
incl.:			
4x KLS 10X20	clamp fastening set		
4x FRSV 10X20	round-head screw with short square, DIN 603		
4x SEMSS 10	hexagon-nut, self-locking, DIN 985		

### Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	L	G
WPV 150F	150 mm	600 mm	1,92 kg
incl.:			
4x KLS 10X20F	clamp fastening set		
4x FRSV 10X20F	round-head screw with short square, DIN 603		
4x SEMB 10F	hexagon-nut, DIN 934		

### Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	L	G
WPV 150E	150 mm	600 mm	1,79 kg



Product	H	L	G
incl. 8x FRSV 10X20E 4x SEM 10E 4x SEMSS 10E			
		round-head screw with short square, DIN 603 hexagon-nut, DIN 934 hexagon-nut, self-locking, DIN 985	

---

**H:** height  
**L:** length  
**G:** weight

