



HS18

Hammerkopfschraube, A 7/A 8/A 9

galvanisch verzinkt gemäß DIN EN ISO 19598 / DIN EN ISO 2081

Artikel	L	Ø	G
HS18 10X30	30 mm	10 mm	5,9 kg/100
HS18 10X40	40 mm	10 mm	6,3 kg/100
HS18 10X50	50 mm	10 mm	6,9 kg/100
HS18 10X60	60 mm	10 mm	7,4 kg/100
HS18 12X30	30 mm	12 mm	7,4 kg/100
HS18 12X40	40 mm	12 mm	7,9 kg/100
HS18 12X60	60 mm	12 mm	9,4 kg/100
HS18 16X40	40 mm	16 mm	13,4 kg/100
HS18 16X60	60 mm	16 mm	16 kg/100
HS18 16X80	80 mm	16 mm	18,8 kg/100

Edelstahl, Werkstoff Nr. 1.4571/1.4404 (V4A)

Artikel	L	Ø	G
HS18 10X30E4	30 mm	10 mm	6 kg/100
HS18 10X40E4	40 mm	10 mm	6,5 kg/100
HS18 10X50E4	50 mm	10 mm	7 kg/100

L: Länge

Seite 1



Ø: Durchmesser
G: Gewicht

DETAILS / ANWENDUNGEN

