



HS22

Hammerkopfschraube, A 2/A 4

galvanisch verzinkt gemäß DIN EN ISO 19598 / DIN EN ISO 2081

Artikel	L	Ø	G
HS22 12X30	30 mm	12 mm	9,5 kg/100
HS22 12X40	40 mm	12 mm	10 kg/100
HS22 12X50	50 mm	12 mm	10,8 kg/100
HS22 12X60	60 mm	12 mm	11,4 kg/100
HS22 16X40	40 mm	16 mm	16,2 kg/100
HS22 16X60	60 mm	16 mm	18,6 kg/100

Tauchfeuerverzinkt, nach DIN EN ISO 1461

Artikel	L	Ø	G
HS22 10X80F	80 mm	10 mm	9,7 kg/100

Edelstahl, Werkstoff Nr. 1.4571/1.4404 (V4A)

Artikel	L	Ø	G
HS22 10X80E4	80 mm	10 mm	9,7 kg/100
HS22 12X30E4	30 mm	12 mm	9,6 kg/100
HS22 12X40E4	40 mm	12 mm	10,1 kg/100
HS22 12X50E4	50 mm	12 mm	10,9 kg/100



Artikel	L	Ø	G
HS22 12X60E4	60 mm	12 mm	11,5 kg/100
HS22 16X40E4	40 mm	16 mm	16,3 kg/100
HS22 16X60E4	60 mm	16 mm	18,7 kg/100

L: Länge
Ø: Durchmesser
G: Gewicht

DETAILS / ANWENDUNGEN

