


LADR

Leiterabzweigdeckel mit Drehriegeln

Deckel für T-Stück.



Sendzimir-feuerverzinkt, nach DIN EN 10346

Artikel	B	R	t	G
LADR 20S	204 mm	398 mm	0,75 mm	2,73 kg
LADR 30S	304 mm	398 mm	1,00 mm	5,20 kg
LADR 40S	404 mm	398 mm	1,00 mm	6,99 kg
LADR 50S	504 mm	398 mm	1,25 mm	11,11 kg
LADR 60S	604 mm	398 mm	1,25 mm	13,74 kg

Tauchfeuerverzinkt, nach DIN EN ISO 1461

Artikel	B	R	t	G
LADR 20F	204 mm	398 mm	0,75 mm	2,91 kg
LADR 30F	304 mm	398 mm	1,00 mm	5,56 kg
LADR 40F	404 mm	398 mm	1,00 mm	7,47 kg
LADR 50F	504 mm	398 mm	1,25 mm	11,89 kg
LADR 60F	604 mm	398 mm	1,25 mm	14,70 kg

Edelstahl, Werkstoff Nr. 1.4301 (V2A)

Artikel	B	R	t	G
LADR 20E	204 mm	398 mm	0,80 mm	2,91 kg

Seite.1



Artikel	B	R	t	G
LADR 30E	304 mm	398 mm	1,00 mm	5,23 kg
LADR 40E	404 mm	398 mm	1,00 mm	7,03 kg
LADR 50E	504 mm	398 mm	1,25 mm	11,18 kg
LADR 60E	604 mm	398 mm	1,25 mm	13,83 kg

B: Breite
R: Radius
t: Materialstärke
G: Gewicht

DETAILS / ANWENDUNGEN

