



RID

Installationsrinnendeckel

Installationsrinnendeckel, formschlüssig einrastend

Sendzimir-feuerverzinkt, nach DIN EN 10346

Artikel	B	L	G
RID 05S	50 mm	3000 mm	1,52 kg
RID 10S	100 mm	3000 mm	2,40 kg
RID 15S	150 mm	3000 mm	3,29 kg
RID 20S	200 mm	3000 mm	4,17 kg
RID 30S	300 mm	3000 mm	7,91 kg

Tauchfeuerverzinkt, nach DIN EN ISO 1461

Artikel	B	L	G
RID 05F	50 mm	3000 mm	1,63 kg
RID 10F	100 mm	3000 mm	2,57 kg
RID 15F	150 mm	3000 mm	3,52 kg
RID 20F	200 mm	3000 mm	4,46 kg
RID 30F	300 mm	3000 mm	8,47 kg

Edelstahl, Werkstoff Nr. 1.4301 (V2A)

Artikel	B	L	G
RID 05E	50 mm	3000 mm	1,63 kg

Seite.1



Artikel	B	L	G
RID 10E	100 mm	3000 mm	2,58 kg
RID 15E	150 mm	3000 mm	3,53 kg
RID 20E	200 mm	3000 mm	4,47 kg
RID 30E	300 mm	3000 mm	7,96 kg

B: Breite
L: Länge
G: Gewicht

DETAILS / ANWENDUNGEN

