

ORDER FORM



KUNEX® clamp joint accessories

BK39

Rev.02 dated: 2023-03-13

Customer:	Project:
Com.:	Element:

The construction of a KUNEX® clamp joint according to general building authority test certificate P-5316/053/14 MPA-BS requires the use of components marked with **◆**.
(One type of crude rubber and fixing each).

Primer

Frankopur 2K **◆**

Consumption: approx 0,3 - 0,5 kg/m²

Container size 1 kg

_____ pcs.

Crude rubber strip




Roll length: 10m **◆**

80 x 4 mm

_____ roll(s)

Clamping rail



Material: galvanized L= 1,45m

V4A L= 1,30m

80 x 8 mm **◆**

_____ pcs.

Punching 16 x 30 mm

80 x 8 mm **◆**

_____ pcs.

Punching 20 x 30 mm



Internal corner

80 x 80 x 10 mm

_____ pcs.

Punching ø 18 mm



External corner

200 x 80 x 10 mm

_____ pcs.

Punching ø 18 mm

Please note page 2

ORDER FORM

KUNEX® clamp joint accessories

BK39

Rev.02 dated: 2023-03-13

Fixing

Requirement per clamping profile:

- Clamping rail, galvanized 10 pcs.
- Clamping rail, V4A 9 pcs.
- Internal corner 1 pcs.
- External corner 3 pcs.

Version 1:



Compound anchor Mungo

M 12 _____ package (10 pcs.)

M 16 ◆ _____ package (10 pcs.)

Anchor rod

(incl. nut and U-washer)

Material: galvanized V4A

M 12/160 _____ packages (10 pcs.)

M 16/190 ◆ _____ packages (10 pcs.)

Version 2:



Concrete bolt ◆

(incl. nut and U-washer)

TSM-B14 M16 galvanized _____ packages
(25 pcs.)

TSM-10x140 M 12x35 _____ packages
(50 pcs.)

Accessories (optional)



Clamping protection profile galvanized incl. fastening material

Length: 2,00 m _____ pcs.

Ordered by: _____

date: _____